

digital wireless for all



Epic digital wireless technology, now amazingly affordable.

Introducing the DWZ Series with affordable 2.4 GHz technology. You get solid-gold 24-bit linear PCM digital audio to keep you sounding your best. You get robust transmission and easy channel selection. Even automatic feedback reduction, encryption and battery charging are available. And Sony has pre-assembled DWZ packages for guitar, vocals, presentation and speech. Sony's DWZ Series. Sound like a million bucks without spending it.

Visit sony.com/proaudio



©2012 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications subject to change without notice. Sony and the Sony make.believe logo are trademarks of Sony. All other trademarks are properties of their respective owners.

the DWZ mics that have your sound

Description	Guitar Set	Vocal Set	Vocal/Speech Set	Headset & Lavalier Set
Package	DWZ-B30GB	DWZ-M50	DWZ-M70	DWZ-B70HL
TX Name	ZTX-B01	ZTX-M01	ZTX-M02RC	ZTX-B02RC
	•High-quality 24-bit Linear PCM digital audio transmission	•High-quality 24-bit Linear PCM digital audio transmission	•High-quality 24-bit Linear PCM digital audio transmission	•High-quality 24-bit Linear PCM digital audio transmission
	Muting function for tuning Lock function protects from	 Sony's original high-quality cardioid dynamic capsule 	AES 128-bit Encryption function	AES 128-bit Encryption function
	inadvertent setting changes•Two AA battery operation	Interchangeable capsule design, with a flexible choice	 Sony's original high-quality cardioid dynamic capsule 	Both cardioid condenser headset microphone &
TX Feature	•Robust metal body	of capsules •Momentary switch for muting	• Interchangeable capsule design, with a flexible choice n	cardioid condenser lavalier microphone are included
		or talk-back application • Lock function protects from	of capsules Latch switch for power on/off 	Momentary switch for muting or talk-back application
		inadvertent setting changes Two AA battery operation 	for conventional operation •Two AA battery operation with	•Two AA battery operation with contactless rechargeable function*
		•Robust metal body	contactless rechargeable function*	•Robust metal body
			Poblist metal body	
DV Norma	702 020		Robust metal body	
RX Name	ZRX-C30	ZRX-HR50	ZRX-HR70	ZRX-HR70
RX Name	ZRX-C30 • 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1)	ZRX-HR50 • 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1)	ZRX-HR70 • Intelligent Feedback reducer function	 Intelligent Feedback reducer function
RX Name	 •3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) •3-way flexible powering 	•3-way parallel audio output ¼″TS phone (2), Balanced	ZRX-HR70 • Intelligent Feedback reducer	Intelligent Feedback reducer
RX Name	 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 3-way flexible powering DC 12V / DC 9V / 9V 6LR61 battery 	 •3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) •5-Band graphic digital 	ZRX-HR70 • Intelligent Feedback reducer function • 3-way parallel audio output ¼" TS phone (2), Balanced	 Intelligent Feedback reducer function 3-way parallel audio output ¼"TS phone (2), Balanced
RX Name	 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 3-way flexible powering DC 12V / DC 9V / 9V 6LR61 battery Cable tone control LED Indicators for status 	 •3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) •5-Band graphic digital equalizer •Color LCD for simple 	ZRX-HR70• Intelligent Feedback reducer function• 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1)• 5-Band graphic digital	 Intelligent Feedback reducer function 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 5-Band graphic digital
	 •3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) •3-way flexible powering •DC 12V / DC 9V / 9V 6LR61 battery •Cable tone control 	 •3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) •5-Band graphic digital equalizer •Color LCD for simple operation & status monitoring for TX & RX •Clear channel scan for easy set up 	ZRX-HR70• Intelligent Feedback reducer function• 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1)• 5-Band graphic digital equalizer• Color LCD for simple operation & status monitoring for TX & RX	 Intelligent Feedback reducer function 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 5-Band graphic digital equalizer Color LCD for simple operation & status monitoring for TX & RX
	 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 3-way flexible powering DC 12V / DC 9V / 9V 6LR61 battery Cable tone control LED Indicators for status monitoring for TX & RX 	 • 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) • 5-Band graphic digital equalizer • Color LCD for simple operation & status monitoring for TX & RX • Clear channel scan for easy 	ZRX-HR70• Intelligent Feedback reducer function• 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1)• 5-Band graphic digital equalizer• Color LCD for simple operation & status monitoring	 Intelligent Feedback reducer function 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 5-Band graphic digital equalizer Color LCD for simple operation & status monitoring
	 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 3-way flexible powering DC 12V / DC 9V / 9V 6LR61 battery Cable tone control LED Indicators for status monitoring for TX & RX 	 •3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) •5-Band graphic digital equalizer •Color LCD for simple operation & status monitoring for TX & RX •Clear channel scan for easy set up •Rackmountable 1U half-rack 	ZRX-HR70• Intelligent Feedback reducer function• 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1)• 5-Band graphic digital equalizer• Color LCD for simple operation & status monitoring for TX & RX• Clear channel scan for easy	 Intelligent Feedback reducer function 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1) 5-Band graphic digital equalizer Color LCD for simple operation & status monitoring for TX & RX Clear channel scan for easy
	 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 3-way flexible powering DC 12V / DC 9V / 9V 6LR61 battery Cable tone control LED Indicators for status monitoring for TX & RX Built-in antenna 	 • 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1) • 5-Band graphic digital equalizer • Color LCD for simple operation & status monitoring for TX & RX • Clear channel scan for easy set up • Rackmountable 1U half-rack size** • Detachable whip antenna 	ZRX-HR70• Intelligent Feedback reducer function• 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1)• 5-Band graphic digital equalizer• Color LCD for simple operation & status monitoring for TX & RX• Clear channel scan for easy set up• Rackmountable 1U half-rack size**• Detachable whip antenna	 Intelligent Feedback reducer function 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 5-Band graphic digital equalizer Color LCD for simple operation & status monitoring for TX & RX Clear channel scan for easy set up Rackmountable 1U half-rack size** Detachable whip antenna
	 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 3-way flexible powering DC 12V / DC 9V / 9V 6LR61 battery Cable tone control LED Indicators for status monitoring for TX & RX 	 • 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) • 5-Band graphic digital equalizer • Color LCD for simple operation & status monitoring for TX & RX • Clear channel scan for easy set up • Rackmountable 1U half-rack size** 	ZRX-HR70• Intelligent Feedback reducer function• 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1)• 5-Band graphic digital equalizer• Color LCD for simple operation & status monitoring for TX & RX• Clear channel scan for easy set up• Rackmountable 1U half-rack size**	 Intelligent Feedback reducer function 3-way parallel audio output ¼" TS phone (2), Balanced XLR (1) 5-Band graphic digital equalizer Color LCD for simple operation & status monitoring for TX & RX Clear channel scan for easy set up Rackmountable 1U half-rack size** Detachable whip antenna Cardioid condenser headset microphone (1) Cardioid condenser lavalier microphone (1) Windscreen (2)
RX Feature	 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 3-way flexible powering DC 12V / DC 9V / 9V 6LR61 battery Cable tone control LED Indicators for status monitoring for TX & RX Built-in antenna 	 • 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) • 5-Band graphic digital equalizer • Color LCD for simple operation & status monitoring for TX & RX • Clear channel scan for easy set up • Rackmountable 1U half-rack size** • Detachable whip antenna Microphone holder (1) Antenna (2) 	 ZRX-HR70 Intelligent Feedback reducer function 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 5-Band graphic digital equalizer Color LCD for simple operation & status monitoring for TX & RX Clear channel scan for easy set up Rackmountable 1U half-rack size** Detachable whip antenna Microphone holder (1) Antenna (2) 	 Intelligent Feedback reducer function 3-way parallel audio output ¼"TS phone (2), Balanced XLR (1) 5-Band graphic digital equalizer Color LCD for simple operation & status monitoring for TX & RX Clear channel scan for easy set up Rackmountable 1U half-rack size** Detachable whip antenna Cardioid condenser headset microphone (1) Cardioid condenser lavalier microphone (1)

* BC-DWZ1 Battery Charger is required

** RMM-HRD1 Rack Mount Kit is required